

AMBER-2X2-W


~50° wide beam

SPECIFICATION:

Dimensions	50.0 x 50.0 mm
Height	8.5 mm
Fastening	glue, pin, screw
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
AMBER-2X2-W	Multi-lens	PMMA	amber		



ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C19175_AMBER-2X2-W » Box size: 480 x 280 x 300 mm	800	160	160	0.0





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):





LED J Series 5050B 6V K Class
FWHM / FWTM 55.0° / 85.0°
Efficiency 72 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.3 %
CCT (LED/with lens)* 3763K/2194K
Required components:



*the measured CCT with lens doesn't follow the Black Body Locus line





LED XP-G3
FWHM / FWTM 53.0° / 80.0°
Efficiency 73 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.4 %
CCT (LED/with lens)* 3838K/2246K
Required components:



Light distribution files






LED LUXEON 5050 HE
FWHM / FWTM 55.0° / 84.0°
Efficiency 72 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.3 %
CCT (LED/with lens)* 3854K/2231K
Required components:



Light distribution files



OPTICAL RESULTS (MEASURED):



OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors



LED OSLON Square CSSRM2/CSSRM3
 FWHM / FWTM 52.0° / 74.0°
 Efficiency 73 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Amount of Blue light (380-500 nm) 0.3 %
 CCT (LED/with lens)* 3898K/2230K
 Required components:



Light distribution files

PHILIPS



LED Fortimo FastFlex LED 2x8 DA G4+
 FWHM / FWTM 54.0° / 80.0°
 Efficiency 67 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files

PHILIPS

LED Fortimo FastFlex LED 2x8 DA G5
 FWHM / FWTM 51.0° / 75.0°
 Efficiency 73 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):

SAMSUNG



LED LH351C
FWHM / FWTM 52.0° / 75.0°
Efficiency 74 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.3 %
CCT (LED/with lens)* 3773K/2232K
Required components:



Light distribution files

SAMSUNG



LED LH502D
FWHM / FWTM 55.0° / 84.0°
Efficiency 72 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.3 %
CCT (LED/with lens)* 3785K/2175K
Required components:



Light distribution files




LED SEOUL DC 5050 6V
FWHM / FWTM 56.0° / 86.0°
Efficiency 72 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.3 %
CCT (LED/with lens)* 3995K/2220K
Required components:



Light distribution files

OPTICAL RESULTS (MEASURED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)