

# **AMY-70-RS**

~13° spot beam with tight cutoff

#### **SPECIFICATION:**

Dimensions	Ø 69.9 mm
Height	11.8 mm
Fastening	socket
ROHS compliant	yes 🕕



#### **MATERIALS:**


Component	Туре	Material	Colour	Finish
AMY-70-RS	Single lens	PMMA	clear	
AMY-70-HLD2-C	Holder C	PC	black	
AMY-70-HLD2-B	Holder B	PC	black	
AMY-70-HLD2-C-WHT	Holder C	PC	white	
AMY-70-HLD2-B-WHT	Holder B	PC	white	



#### **ORDERING INFORMATION:**

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C18516_AMY-70-RS	285	285	15	9.7
Assembly				
CP19121_AMY-70-RS-B2-WHT	210	210	15	9.0
CP19112_AMY-70-RS-C2-WHT	210	210	15	8.8
CP19105_AMY-70-RS-B2	210	210	15	9.0
CP19045_AMY-70-RS-C2	210	210	15	8.8

# PRODUCT DATASHEET AMY-70-RS



See also our general installation guide: www.ledil.com/installation\_guide




bridgelux

LED V18 Gen 8-9

Ordering code CP19045\_AMY-70-RS-C2

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 24.0° / 52.0° Efficiency 82 % Peak intensity 2.8 cd/lm LEDs/each optic Light colour White Required components:

Bender Wirth: 639b Hekla XL



bridgelux


LED V3 HD Gen 8

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 6.0° / 14.0° Efficiency 93 % 33.7 cd/lm Peak intensity LEDs/each optic 1 White Light colour

Required components:

F15253\_HEKLA-SOCKET-A



bridgelux


LED V3 HD Gen 8 FC

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 6.0° / 12.0° Efficiency 92 % Peak intensity 39.7 cd/lm LEDs/each optic 1

Light colour White Required components:

F15255\_HEKLA-SOCKET-C




bridgelux

LED V4 HD Gen 8

CP19045\_AMY-70-RS-C2 Ordering code

FWHM / FWTM 8.0° / 14.0° 93 % Efficiency Peak intensity 27.6 cd/lm LEDs/each optic White Light colour Required components:

F15253\_HEKLA-SOCKET-A






bridgelux

LED V6 Gen 8-9

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 18.0°
Efficiency 95 %
Peak intensity 18.2 cd/lm
LEDs/each optic 1
Light colour White

Required components: F15253\_HEKLA-SOCKET-A



bridgelux

LED V6 Gen 8-9

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 18.0°

Efficiency 92 %


Peak intensity 18.2 cd/lm

LEDs/each optic 1

Light colour White

Required components:

F15253\_HEKLA-SOCKET-A



bridgelux


LED V6 HD Gen 8

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 18.0°
Efficiency 91 %
Peak intensity 17.8 cd/lm
LEDs/each optic 1
Light colour White

Required components:

F15255\_HEKLA-SOCKET-C




bridgelux

LED V9 HD Gen 8

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 12.0° / 22.0°
Efficiency 90 %
Peak intensity 12.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15859\_HEKLA-SOCKET-I






#### bridgelux

LED VERO18

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 28.0° / 56.0°
Efficiency 86 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C16142\_HEKLA-SOCKET-K



#### bridgelux

LED Vesta DTW 13mm (21W)
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 20.0°

Efficiency 91 %


Peak intensity 15.7 cd/lm

LEDs/each optic 1

Light colour White

Required components:

Bender Wirth: 632b Hekla XL



#### bridgelux


 LED
 Vesta DTW 15mm (33W)

 Ordering code
 CP19045\_AMY-70-RS-C2

FWHM / FWTM 20.0° / 40.0°
Efficiency 87 %
Peak intensity 4.7 cd/lm
LEDs/each optic 1
Light colour White

Required components:

Bender Wirth: 632b Hekla XL




#### bridgelux

LED Vesta DTW 6mm

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 20.0°
Efficiency 91 %
Peak intensity 15.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:

Bender Wirth: 652b Hekla





bridgelux


LED Vesta SE 13mm TW
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 20.0° / 37.0°
Efficiency 82 %
Peak intensity 4.7 cd/lm
LEDs/each optic 1

Light colour Tunable White

Required components:

C16142\_HEKLA-SOCKET-K



bridgelux

LED Vesta TW 13mm (18W) DP Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 23.0° / 46.0°

Efficiency 85 %

Peak intensity 3.3 cd/lm


LEDs/each optic 1

Light colour White

Required components:

C16142\_HEKLA-SOCKET-K F18158\_HEKLA-RZ-LENS

Bender Wirth: 492 Typ L8




bridgelux

LED Vesta TW 9mm (9W) DP
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 15.0° / 29.0°
Efficiency 92 %
Peak intensity 7.5 cd/lm
LEDs/each optic 1
Light colour White

Required components: C16142\_HEKLA-SOCKET-K Bender Wirth: 489 Typ L8




**CITIZEN** 

 LED
 CLL02x/CLU02x (LES10)

 Ordering code
 CP19105\_AMY-70-RS-B2

FWHM / FWTM 14.0° / 26.0°
Efficiency 86 %
Peak intensity 9 cd/lm
LEDs/each optic 1
Light colour White
Required components:






# **CITIZEN**

 LED
 CLL02x/CLU02x (LES10)

 Ordering code
 C18516\_AMY-70-RS

FWHM / FWTM 14.0° / 26.0°
Efficiency 86 %
Peak intensity 9 cd/lm
LEDs/each optic 1
Light colour White

Required components:




# **CITIZEN**

 LED
 CLL02x/CLU02x (LES10)

 Ordering code
 CP19045\_AMY-70-RS-C2

FWHM / FWTM 14.0° / 26.0°
Efficiency 86 %
Peak intensity 9 cd/lm
LEDs/each optic 1
Light colour White

Required components:




# CREE +

LED CHA0304

Ordering code CP19112\_AMY-70-RS-C2-WHT

FWHM / FWTM 6.0° / 12.0°
Efficiency 94 %
Peak intensity 39.7 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17435\_HEKLA-G2-C






LED CHA0410

Ordering code CP19112\_AMY-70-RS-C2-WHT

FWHM / FWTM 8.0° / 14.0°
Efficiency 94 %
Peak intensity 29.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:

Required components: F17435\_HEKLA-G2-C






# CREE -

LED CMA1840

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 20.0° / 39.0°
Efficiency 85 %
Peak intensity 4.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:

Required components: Bender Wirth: 637a Hekla



# CREE \$

LED CMT14xx

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 14.0° / 26.0°

Efficiency 87 %


Peak intensity 9.2 cd/lm

LEDs/each optic 1

Light colour White

Required components:

Required components: F17435\_HEKLA-G2-C




# CREE +

LED CMT14xx

Ordering code C18516\_AMY-70-RS

FWHM / FWTM 14.0° / 25.0°
Efficiency 93 %
Peak intensity 9.8 cd/lm
LEDs/each optic 1
Light colour White

Required components:






LED CMU10xx

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 12.0° / 25.0°
Efficiency 89 %
Peak intensity 10 cd/lm
LEDs/each optic 1
Light colour White

Required components: BJB: 47.360.1020






# CREE &

LED CMU15xx

Ordering code CP19045\_AMY-70-RS-C2

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 20.0° / 38.0° Efficiency 85 % Peak intensity 4.6 cd/lm LEDs/each optic Light colour White Required components:

F17438\_HEKLA-G2-I




# CREE \$

LED CMU15xx

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 20.0° / 40.0° Efficiency 85 % 4.4 cd/lm Peak intensity LEDs/each optic 1 White Light colour Required components:

Bender Wirth: 633a Hekla




# LUMILEDS

LED LUXEON CX Plus CoB L08 (Gen2)

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 22.0° / 40.0° Efficiency 89 % Peak intensity 4.2 cd/lm LEDs/each optic 1 White Light colour Required components:

Bender Wirth: 637a Hekla




# **MUMILEDS**

LED LUXEON 7070 FWHM / FWTM 9.0° / 18.0° Efficiency 94 % 19.8 cd/lm Peak intensity LEDs/each optic White

Required components:

Light colour






### **LUMILEDS**

LED LUXEON CoB 1202/1203 Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 12.0° / 24.0° Efficiency 90 % Peak intensity 10.8 cd/lm LEDs/each optic Light colour White Required components:

F15858\_HEKLA-SOCKET-H




### LUMILEDS

LUXEON CoB 1202HD Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 20.0° Efficiency 92 % 16.2 cd/lm Peak intensity LEDs/each optic 1 White Light colour Required components:

F15848\_HEKLA-SOCKET-G




# LUMILEDS

LED LUXEON CoB 1204/1205 Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 20.0° / 36.0° Efficiency 88 % Peak intensity 5.2 cd/lm LEDs/each optic 1 White Light colour Required components:

Bender Wirth: 632a Hekla XL




# **MUMILEDS**

LED LUXEON CoB 1204HD CP19045\_AMY-70-RS-C2 Ordering code

FWHM / FWTM 14.0° / 25.0° 90 % Efficiency Peak intensity 9.7 cd/lm LEDs/each optic White Light colour Required components:

F15858\_HEKLA-SOCKET-H






### **MUMILEDS**

LED LUXEON CoB 1205HD
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 18.0° / 30.0°
Efficiency 89 %
Peak intensity 6.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15858\_HEKLA-SOCKET-H




# **MATERIAL PROPERTY OF THE PROP**

LED LUXEON CoB 1208
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 21.0° / 40.0°
Efficiency 88 %
Peak intensity 4.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:

Bender Wirth: 632a Hekla XL



# **MUMILEDS**


LED LUXEON CX Plus CoB - HD S02H6

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 10.0° / 19.0°
Efficiency 92 %
Peak intensity 17.6 cd/lm
LEDs/each optic 1
Light colour White

Required components:

Bender Wirth: 634c Bayonet35L




# **DIVIDITION**

LED LUXEON CX Plus CoB - HD S04H9

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 14.0° / 26.0°
Efficiency 91 %
Peak intensity 9.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:

Bender Wirth: 634a Bayonet35L






### **MUMILEDS**

LED LUXEON CX Plus CoB L04 / L05 (Gen2)

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 16.0° / 32.0°
Efficiency 89 %
Peak intensity 6.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15254\_HEKLA-SOCKET-B



# LUMILEDS

LED LUXEON CX Plus CoB M02 / M03 (Gen2)

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 14.0° / 26.0°
Efficiency 91 %
Peak intensity 9.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15256\_HEKLA-SOCKET-D

# **DESCRIPTION**


LED LUXEON CX Plus CoB S01 (Gen2)

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 18.0°
Efficiency 92 %
Peak intensity 18.8 cd/lm
LEDs/each optic 1
Light colour White

Required components:

F15956\_HEKLA-SOCKET-J




# **ELUMINUS**

LED CHM-9 XH (19x19)

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 12.0° / 24.0°
Efficiency 91 %
Peak intensity 11.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15859\_HEKLA-SOCKET-I





#### **ELUMINUS**


LED CTM-14 (Tunable White) Gen2 Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 20.0° / 36.0° Efficiency 89 % Peak intensity 5.1 cd/lm LEDs/each optic

Light colour Tunable White

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 442 Typ L8



#### **ELUMINUS**

LED CTM-6 (Tunable White) Gen2 Ordering code CP19045\_AMY-70-RS-C2


FWHM / FWTM 10.0° / 20.0° Efficiency 92 % 16.2 cd/lm Peak intensity

LEDs/each optic 1

Tunable White Light colour

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 495 Typ L8



# **ELUMINUS**


LED CTM-9 (Tunable White) Gen2 Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 12.0° / 24.0° Efficiency 90 % Peak intensity 10.6 cd/lm LEDs/each optic

Tunable White Light colour

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 495 Typ L8




# **ELUMINUS**

LED CxM-14 (18.5x18.5) CP19045\_AMY-70-RS-C2 Ordering code

FWHM / FWTM 22.0° / 41.0°

86 % Efficiency Peak intensity 4 cd/lm LEDs/each optic White Light colour

Required components: F17438\_HEKLA-G2-I






#### **ELUMINUS**

LED CXM-3

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 6.0° / 12.0°
Efficiency 93 %
Peak intensity 38 cd/lm
LEDs/each optic 1
Light colour White
Required components:

Bender Wirth: 634a Bayonet35L



#### **ELUMINUS**

LED CXM-4

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 8.0° / 15.0°

Efficiency 92 %


Peak intensity 27.9 cd/lm

LEDs/each optic 1

Light colour White

Required components:

Bender Wirth: 634a Bayonet35L



# LUMINUS


LED CxM-6 (13.5x13.5)

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 10.0° / 18.0°
Efficiency 92 %
Peak intensity 18.2 cd/lm
LEDs/each optic 1

Light colour White Required components:

BJB: 47.360.1020




# **WNICHIA**

LED COB J-Type

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 21.0° / 40.0°
Efficiency 89 %
Peak intensity 4.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:

Bender Wirth: 663a Hekla XL






### **WNICHIA**

LED COB L-Type (LES 11)
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 16.0° / 30.0°
Efficiency 90 %
Peak intensity 7.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15858\_HEKLA-SOCKET-H




### **WNICHIA**

LED COB S-Type (LES 6)
Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 8.0° / 18.0°
Efficiency 92 %
Peak intensity 20.4 cd/lm
LEDs/each optic 1
Light colour White

Required components:

Bender Wirth: 652a Bayonet35L




#### **W**NICHIA

LED COB S-Type (LES 7)
Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 10.0° / 20.0°
Efficiency 92 %
Peak intensity 16.6 cd/lm
LEDs/each optic 1
Light colour White

Required components:

Bender Wirth: 652a Bayonet35L



### **WNICHIA**


Required components:

LED COB T-Type

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 10.0° / 18.0°
Efficiency 92 %
Peak intensity 18.6 cd/lm
LEDs/each optic 1
Light colour White

Bender Wirth: 652a Bayonet35L





#### **WNICHIA**

LED NJCWL024Z-V1MT: COB L-Type Tunable White


Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 10.0° / 20.0° Efficiency 91 % Peak intensity 15.1 cd/lm LEDs/each optic 1

Light colour Tunable White

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 497 Typ L8 HV



#### **WNICHIA**

LED NJNWS012Z-V1MT: COB S-Type Tunable White

Ordering code CP19045\_AMY-70-RS-C2

 FWHM / FWTM
 8.0° / 16.0°

 Efficiency
 92 %

 Peak intensity
 23.8 cd/lm


 L EDa/gook patie
 1

LEDs/each optic 1

Light colour Tunable White

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 495 Typ L8 HV



#### **WNICHIA**

LED NVCWJ024Z-V1MT: COB J-Type Tunable White


Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 14.0° / 28.0° Efficiency 90 % Peak intensity 8.1 cd/lm LEDs/each optic 1

Light colour Tunable White

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 498 Typ L8 HV




# **SAMSUNG**

LED LC003D / LC006D / LC009D / LC013D

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 14.0° / 26.0°
Efficiency 91 %
Peak intensity 9.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:

BJB: 47.360.1020






# **SAMSUNG**

LED LC010C G2

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 10.0° / 18.0°
Efficiency 92 %
Peak intensity 19.3 cd/lm
LEDs/each optic 1
Light colour White

Required components: BJB: 47.360.1020



# SAMSUNG

LED LC010T (Tunable White)
Ordering code CP19045\_AMY-70-RS-C2

 FWHM / FWTM
 12.0° / 22.0°


 Efficiency
 91 %

 Peak intensity
 12.9 cd/lm

LEDs/each optic 1

Light colour Tunable White

Required components: Bender Wirth: 501 Typ L8




# **SAMSUNG**

LED LC016D / LC019D / LC026D / LC033D

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 20.0° / 40.0°
Efficiency 85 %
Peak intensity 4.3 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17438\_HEKLA-G2-I




# **SAMSUNG**

LED LC020C G2

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 12.0° / 24.0°
Efficiency 90 %
Peak intensity 11.4 cd/lm
LEDs/each optic 1
Light colour White

Required components: BJB: 47.360.1010





# **SAMSUNG**


LED LC020T (Tunable white)
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 16.0° / 30.0° Efficiency 90 % Peak intensity 6.8 cd/lm LEDs/each optic 1

Light colour Tunable White

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 501 Typ L8




# **SAMSUNG**

LED LC030C/040C G2

Ordering code CP19105\_AMY-70-RS-B2

FWHM / FWTM 16.0° / 32.0°
Efficiency 89 %
Peak intensity 6.7 cd/lm
LEDs/each optic 1
Light colour White

Required components: BJB: 47.360.1010




SEOUL SEMICONDUCTOR

LED MJT COB LES 14.5
Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 22.0° / 40.0°
Efficiency 88 %
Peak intensity 4.3 cd/lm
LEDs/each optic 1
Light colour White

Required components: F15859\_HEKLA-SOCKET-I






LED MJT COB LES 6

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 8.0° / 18.0°
Efficiency 93 %
Peak intensity 20.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15255\_HEKLA-SOCKET-C








LED MJT COB LES 9.8

Ordering code CP19045\_AMY-70-RS-C2

FWHM / FWTM 14.0° / 26.0°
Efficiency 91 %
Peak intensity 9.4 cd/lm
LEDs/each optic 1
Light colour White

F15255\_HEKLA-SOCKET-C

Required components:





# PRODUCT DATASHEET AMY-70-RS

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where to buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where\_to\_buy