	т	<u>ح</u>	<u> </u>		ш		D			C		
3 4	3.5 8.84±0.4	CP18440_AMY-35-WA CP19603_AMY-35-WA		<u>0</u> 1	rientation ri) b						
	Beam dir	Section	¢35	±0.3			Connector <u>BJB / B+W 3</u>	<u>5mm-in</u>	<u>terf</u>	ace		
9				INDEX 1 2	PART AMY-35-WAS C18439_AMY-35-V HOLDER B	WAS		TYPE LENS HOLDER	1	MATERIAL PMMA	COLOU	
				2	C19997_AMY-35-I		P-B-ASYM-W	TIOLDEN	+ +	PC	BLACK	_
	Orientation	rib / /			C19998_AMY-35-I					PC	WHITE	
	Screw holes:									ì		
			PRODUCT AMY - 35 - WAS						ANGLE			
-	Notes PCB or heatsink LED location Ensure LED fitt www.ledil.com	· · ·	model available from				according to DIN 16 if not otherwise sh Silicone moulding g according to ISO 33 and applies if not the drawing.	own in the eneral tol 02-1 Class	n in the drawing. eral tolerances -1 Class M3		-	/
		s about installation please see	e LEDiL Installation Guide on				SCALE 2	:1		WEIG	HT -	
L L	Н	G								<u> </u>		



