

## DAHIA-W

~90° wide beam

## SPECIFICATION:

Dimensions	321.0 x 80.5
Height	11 mm
Fastening	screw
Ingress protection classes	IP66,IP67
ROHS compliant	yes ⓘ


## MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
DAHIA-W	Multi-lens	PMMA	clear		
DAHIA-TL-SEAL	Seal	Silicone			



## ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CS19420_DAHIA-W	80	80	4	8.6
» Box size: 343 x 343 x 298 mm				




See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### OPTICAL RESULTS (MEASURED):

#### CEZOS



LED L0-278053-HW-C2800-K414  
FWHM / FWTM 86.0° / 113.0°  
Efficiency 96 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

#### CEZOS


LED L0-278053-RGBW-C2000-K409  
FWHM / FWTM 83.0° / 108.0°  
Efficiency 95 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour/type RGBW  
Required components:



Light distribution files

#### CEZOS

LED L0-278053-RGBW-C2100-K411  
FWHM / FWTM 95.0° / 139.0°  
Efficiency 92 %  
Peak intensity 0.4 cd/lm  
LEDs/each optic 1  
Light colour/type RGBW  
Required components:





Light distribution files

#### OPTICAL RESULTS (MEASURED):





LED LUXEON C  
FWHM / FWTM 95.0° / 139.0°  
Efficiency 92 %  
Peak intensity 0.4 cd/lm  
LEDs/each optic 1  
Light colour/type RGBW  
Required components:



Light distribution files




LED OSLO Pure 1414  
FWHM / FWTM 83.0° / 108.0°  
Efficiency 95 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour/type RGBW  
Required components:



Light distribution files



LED OSLO Square GW CSSRM4.HW  
FWHM / FWTM 86.0° / 113.0°  
Efficiency 96 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files



## OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors

LED	OSLON Square GW CSSRM4.HW
FWHM / FWTM	86.0° / 109.0°
Efficiency	87 %
Peak intensity	0.5 cd/Im
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24100 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)