

DATE  
27.04.2022

Maximum height of connectors  
3.1mm

LED package c-c 1.8mm

LED pitch 20mm

The connectors must have  
a minimum distance of 0.4mm  
from the keep away area

Connector for reference:  
Molex 2038638103

Keep away area hatched

Cutouts for wiring

V cut for cutting the PCB to units


PART  
DAISY-MINI-3X1 2LED\_REFERENCE-PCB\_002

MECHANICAL DRAWING

PRODUCT  
DAISY-MINI-3X1

Plastic moulding general tolerances  
according to DIN 16901-130 and applies  
if not otherwise shown in the drawing.  
Silicone moulding general tolerances  
according to ISO 3302-1 Class M3  
and applies if not otherwise shown in  
the drawing.

FIRST ANGLE PROJECTION:



**LEDiL**®

This drawing is the property  
of LEDiL Oy. It may not be  
copied or otherwise  
distributed without prior written  
permission from LEDiL Oy.

SCALE 1:1

WEIGHT -

A3 SHEET 1/1

Notes

Ensure LED fitting from a product specific 3D model available from  
[www.ledil.com](http://www.ledil.com)  
For more details about installation please see LEDiL Installation Guide on  
[www.ledil.com](http://www.ledil.com)