HEATSINK LEVEL

① 7.85 ±0.25

0.15

④ 1.2 ±0.25

⑤ 5.95 ±0.25

② 1.7 ±0.2

③ 3.35 ±0.2

NOTE:
C19950_HEKLA-SOCKET-RZ has
0,6mm higher top surface than
other HEKLA sockets.
(Dimension 5).

⑨ ⌀3.52 ±0.2

2x

⑦ 24.5 ±0.25

⑧ 19.6 ±0.25

⑥ 30.05 ±0.25

⑪ ⌀39.48 ±0.3

⑩ ⌀44.74 ±0.3

⌀48.67 ±0.3

A

A

Notes

🔴 PCB or heatsink level.

🟢 LED location

Ensure LED fitting from a product specific 3D model available from www.ledil.com

For more details about installation please see LEDiL Installation Guide on www.ledil.com

PART		MATERIAL	COLOR / COATING
C19950_HEKLA-SOCKET-RZ_011_MechanicalModel_001		PC	clear

MECHANICAL DRAWING

PRODUCT
HEKLA

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:

LEDiL

SCALE	1:1	WEIGHT	4 g	A3	SHEET 1/1