PRODUCT DATASHEET CS17090_HB-IP-2X6-M-PC

HB-IP-2X6-M-PC

~25° medium beam. Variant made from PC.

SPECIFICATION:

Dimensions 173.0 x 71.4 mm

Height 11.4 mm

Fastening pin, screw

Ingress protection classes IP67

ROHS compliant yes 1



MATERIALS:

ComponentTypeMaterialColourFinishHB-IP-2X6-M-PCMulti-lensPCclear2X6-SEAL25SealSiliconewhite

ORDERING INFORMATION:

 Component
 Qty in box
 MOQ
 MPQ
 Box weight (kg)


 CS17090_HB-IP-2X6-M-PC
 Multi-lens
 120
 40
 40
 8.3

 » Box size: 476 x 273 x 247 mm
 8.3
 8.3
 8.3

Published: 28/06/2019



PRODUCT CS17090_HB-IP-2X6-M-PC




See also our general installation guide: www.ledil.com/installation_guide

Published: 28/06/2019



OPTICAL RESULTS (MEASURED):



PRODUCT DATASHEET CS17090_HB-IP-2X6-M-PC


OPTICAL RESULTS (SIMULATED):



LED NV4WB35AM
FWHM / FWTM 34.0° / 64.0°
Efficiency 89 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1

Required components:

Light colour




OSRAM

LED PrevaLED Brick HP IP 2x6

White

FWHM / FWTM 28.0° / 58.0°
Efficiency 89 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White

Required components:




OSRAM Opto Semiconductors

LED OSCONIQ P 3737 (2W version)

FWHM / FWTM 24.0° / 53.0°
Efficiency 89 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour White


Required components:



OSRAM


LED OSLON Square CSSRM2/CSSRM3

FWHM / FWTM 26.0° / 54.0°
Efficiency 89 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (SIMULATED):





PRODUCT DATASHEET CS17090_HB-IP-2X6-M-PC

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405, Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

6/6

www.ledil.com/ where_to_buy