

DATE
29.02.2024

NOTE. Only one round hole in each PCB

Wire connector solder
pad center points
WAGO 2065
8mmx2,3mm, 2,7 mm
height

144 x LED center points

3 x 279.9 ± 0.1 c/c
Position pin holes

15.55 ± 0.1

279.9 ± 0.1

139.95 ± 0.1

Ø 2 ± 0.1

14.8 ± 0.1

26 ± 0.1

2

2

279.85 ± 0.1

4

3

45.2

45.2

62.2 ± 0.1

Ø 3.3

6

7.4

279.85 ± 0.1

8 x Screw hole for
PCB attachment

1119.5 ± 0.2

Front view
Scale: 1:4


LED 1 X 2835
180° rotation

MECHANICAL DRAWING

PRODUCT
LIANNA-2R 4ft-26mm-PCB reference

Plastic moulding general tolerances
according to DIN 16901-130 and applies
if not otherwise shown in the drawing.
Silicone moulding general tolerances
according to ISO 3302-1 Class M3
and applies if not otherwise shown in
the drawing.

FIRST ANGLE PROJECTION:



SCALE 1:1

WEIGHT -

LEDiL

This drawing is the property
of LEDiL Oy. It may not be
copied or otherwise
distributed without prior written
permission from LEDiL Oy.

A3 SHEET 1/1