

### LEILA

#### Lenses for general, wall-washing and sports lighting

LEDiL's well-established LEILA family with symmetric and asymmetric beams. LEILA-G2 comes with a thinner holder design and is backwards compatible with previous generations. The wall-washing beam is designed to be used in groups to provide uniform illumination with a typical installation distance from the wall of 10-20 cm and optimal luminaire spacing of 5-15 cm.


### LEILA

Ø21.6 mm lenses, optimised for 3535 and compatible with up to 5050 size LED packages



### PRODUCTS:


#### CA14508\_G2-LXP2-D



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~14° diffused spot beam with light, black holder. Assembly with installation tape.


#### CP11632\_LXP3-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly.

#### LR1-D




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~14° diffused spot beam optimized for LUXEON Rebel. 14.3 mm high assembly.

### PRODUCTS:


#### CA12665\_LXB2-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~14° diffused spot beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.


#### FA10661\_LXP-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### CA12264\_LR2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.40 mm**

~25° medium beam optimized for LUXEON Rebel. 14.4 mm high assembly with installation tape.


#### CA14507\_G2-LXP2-D-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~14° diffused spot beam with light, black holder. Assembly with location pins and installation tape.


#### CP11631\_LXP3-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly.

#### LE1-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 15.10 mm**

~9.6° spot beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.

### PRODUCTS:


#### CA12629\_LR2-O-90



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~10° x 40° oval beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape. Variant with beam direction rotated 90°.


#### FA10660\_LXP-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### CA12263\_LR2-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.40 mm**

~14° diffused spot beam optimized for LUXEON Rebel. 14.4 mm high assembly with installation tape.


#### CA14506\_G2-LXP2-RS2



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~8.5° spot beam with light, black holder. Assembly with installation tape.

#### CA11484\_LXP2-O-90



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with beam direction rotated 90°.


#### LE1-M

**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 15.10 mm**

~25° medium beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.

### PRODUCTS:


#### CP12416\_LOS-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~40° wide beam optimized for Osram  
Oslon Square EC. 14.3 mm high  
assembly.


#### FA10653\_LC1-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 16.50 mm**

~9.6° spot beam optimized for CREE  
XR-E. 16.5 mm high assembly with  
installation tape.


#### CA12262\_LR2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~9.6° spot beam optimized for LUXEON  
Rebel. 14.3 mm high assembly with  
installation tape.


#### CA14505\_G2-LXP2-RS2-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~8.5° spot beam with light, black holder.  
Assembly with location pins and  
installation tape.


#### CA11483\_LXP2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~25° medium beam optimized for CREE  
XP-E. 14.7 mm high assembly with  
installation tape.

#### FA10753\_LO2-D




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~14° diffused spot beam optimized for  
Osram Golden Dragon+. 14.6 mm high  
assembly with installation tape.

### PRODUCTS:


#### CP12415\_LOS-O-90



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~10° x 40° oval beam optimized for Osram Oslon Square EC. 14.3 mm high assembly. Variant with beam direction rotated 90°.


#### FA10652\_LC1-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 16.50 mm**

~25° medium beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.


#### FA11939\_LXM-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~25° medium beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.


#### CA14503\_G2-LXP2-RS-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with thin holder with pins.


#### CA11482\_LXP2-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

#### FA10751\_LO2-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~9.6° spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

### PRODUCTS:


#### CP12414\_LOS-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~25° medium beam optimized for Osram  
Oslon Square EC. 14.3 mm high  
assembly.


#### CA16435\_LXP2-SS-WAS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.72 mm**

Asymmetric beam. Assembly with  
installation tape.


#### FA10650\_LM1-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~14° diffused spot beam optimized for  
CREE MC-E. 14.04 mm high assembly  
with installation tape.


#### FA11937\_LXM-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~9.6° spot beam optimized for CREE  
XM-L. 14.8 mm high assembly with  
installation tape.


#### CA14392\_LXP2-O-WAS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

Asymmetric beam for wall-washing and  
optimized for CREE XP-E. 14.6 mm high  
assembly with installation tape.

#### CA11481\_LXP2-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~9.6° spot beam optimized for CREE  
XP-E. 14.7 mm high assembly with  
installation tape.

### PRODUCTS:


#### FA10750\_LO2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~25° medium beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.


#### CP12413\_LOS-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~14° diffused spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


#### CA15772\_G2-LXP2-W-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~40° wide beam with light, black holder. Assembly with location pins and installation tape.


#### FA10614\_LM1-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~25° medium beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.


#### CA11931\_LR2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~25° medium beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.

#### CP13059\_LOS-RS2




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~8.5° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

### PRODUCTS:


#### FA11450\_LXP-M2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~30° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### FA10698\_LN2-REC



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.50 mm**

~35° x 25° rectangular beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.


#### CP12412\_LOS-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~9.6° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


#### CA14512\_G2-LXP2-O-90



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with beam direction rotated 90°. Variant with thin holder.


#### FA10613\_LM1-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~20° spot beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

#### CA11930\_LR2-D




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~14° diffused spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.



### PRODUCTS:

#### CP12817\_LXP3-RS2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~8.5° spot beam optimized for CREE  
XP-E. 14.7 mm high assembly.


#### CA11136\_LO2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.90 mm**

~40° wide beam optimized for Osram  
Golden Dragon+. 13.9 mm high  
assembly with installation tape.


#### FA10697\_LN2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.50 mm**

~25° medium beam optimized for Nichia  
NS6x83. 13.3 mm high assembly with  
installation tape.


#### CP12395\_LXP3-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~40° wide beam optimized for CREE  
XP-E. 14.7 mm high assembly.


#### CA14511\_G2-LXP2-O-90-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~10° x 40° oval beam optimized for  
CREE XP-E. 14.7 mm high assembly  
with installation tape. Variant with beam  
direction rotated 90°. Variant with thin  
holder with pins.

#### CA11929\_LR2-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~9.6° spot beam optimized for LUXEON  
Rebel ES. 14.8 mm high assembly with  
installation tape.

### PRODUCTS:


#### FA11116\_LXP-O-90



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### CA12816\_LXP2-RS2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### FA10696\_LN2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.50 mm**

~9.6° spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.


#### CA12394\_LR2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~40° wide beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


#### CA14510\_G2-LXP2-M



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~20° medium beam with light, black holder. Assembly with installation tape.

#### FA11894\_LM1-W




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~40° wide beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

### PRODUCTS:


#### LR1-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~40° wide beam optimized for LUXEON Rebel. 14.3 mm high assembly.


#### CA12667\_LXB2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~40° wide beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.


#### FA10695\_LN2-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.50 mm**

~14° diffused spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.


#### CA12393\_LR2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.50 mm**

~40° wide beam optimized for LUXEON Rebel. 14.5 mm high assembly with installation tape.


#### CA14509\_G2-LXP2-M-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~20° medium beam with light, black holder. Assembly with location pins and installation tape.

#### FA11739\_LXP-RS2




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

### PRODUCTS:


#### FA10832\_LXP-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~40° wide beam optimized for CREE  
XP-E. 14.7 mm high assembly with  
installation tape.


#### CA12666\_LXB2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~25° medium beam optimized for CREE  
XB-D. 14.6 mm high assembly with  
installation tape.


#### FA10663\_LXP-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~14° diffused spot beam optimized for  
CREE XP-E. 14.7 mm high assembly  
with installation tape.

#### CA12392\_LXP2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~40° wide beam optimized for CREE  
XP-E. 14.7 mm high assembly with  
installation tape.

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)