	C19887_TINA-Y-WWW	Recommend
4		
		Clip reference
S	L20165_TINA-Y-SC2-HLD 16.17	15.
		C18696_SOLDER-C Bottom of solde Opening of sold
2		
		LP20174_TINA-Y-SC2-WWW COMPONENTS INDEX PART TYP 1 C10887_TINA_X_WMMU
		1         C19887_TINA-Y-WWW         LEN           2         L20165_TINA-Y-SC2-HLD         HOL
		MECHANICAL DRAWING
		PRODUCT TINA-Y-SC2-WWW
F	PCB or heatsink level.         LED location         Ensure LED fitting from a product specific 3D model available from         www.ledil.com	Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.
	For more details about installation please see LEDiL Installation Guide on www.ledil.com	SCALE 3:1 WEIGHT -
	H G H	

ш

ш

Δ

ပ

т

G

$ \begin{array}{c} 13\\ 0\\ 1\\ 0\\ 1\\ 0\\ 1\\ 0\\ 1\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\$	gn	4
rence distance after soldering		
15.5±0.20 DLDER-CLIP-2 solder clip underneath holder of solder clip facing holder		
TYPE COUNT MA	TERIAL COLOR / COATING	
HOLDER 1 PC		
W LEDIL		
This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.		1
HT -	A3 SHEET 1/1	
В	A	

Recommended PAD design