



C11004_TINA2-RS

L20167_TINA-SC2-HLD


Recommended PAD design



Clip reference distance after soldering



C18696_SOLDER-CLIP-2
Bottom of solder clip underneath holder
Opening of solder clip facing holder



LP20183_TINA-SC2-RS

COMPONENTS

INDEX	PART	TYPE	COUNT	MATERIAL	COLOR / COATING
1	C11004_TINA2-RS	LENS	1	PMMA	CLEAR
2	L20167_TINA-SC2-HLD	HOLDER	1	PC	BLACK


MECHANICAL DRAWING

PRODUCT
TINA-SC2-RS

LEDiL

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:





This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 3:1

WEIGHT -

A3 SHEET 1/1

 	Notes
	PCB or heatsink level.
	LED location
	Ensure LED fitting from a product specific 3D model available from www.ledil.com For more details about installation please see LEDiL Installation Guide on www.ledil.com