

H G F E D C B A

Connector example:
Wago 2016-452

281

0.9

Scale: 1:1

140.5

123.6

61.8

61.8

123.6

Wires through cooler profile

2.6

13

6.7

11x20,6=226.5

Ø 3.4 (Screw holes 5x)

Max. 6,8 mm

19.2

Led: Nichia NCSU 334A

123.8

6.7

123.8

6.7

R1.7

Scale: 1:1


Scale: 1:1

Ø 3.4
(Position pin hole)

1.2

Position pin hole (2x)

PART	TYPE	MATERIAL	COLOR / COATING
Violet_PCB_		Al-base	

MECHANICAL DRAWING		LEDiL®
PRODUCT	VIOLET	
Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.	FIRST ANGLE PROJECTION: 	This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.
SCALE	1:1	WEIGHT -
		A3 SHEET 1/1

Notes

● PCB or heatsink level.
LED location
Ensure LED fitting from a product specific 3D model available from www.ledil.com
For more details about installation please see LEDiL Installation Guide on www.ledil.com

H G B A