

LED position coordinates


1st circle		
REF.	X	Y
1	-0,82	-54,99
2	15,43	-52,79
3	30,3	-45,9
4	42,49	-34,93
5	50,89	-20,85
6	54,78	-4,92
7	53,8	11,44
8	48,03	26,79
9	38	39,76
10	24,6	49,16
11	9	54,29
12	-7,39	54,5
13	-23,13	49,9
14	-36,81	40,87
15	-47,22	28,2
16	-53,43	13,03
17	-54,9	-3,3
18	-51,49	-19,33
19	-43,51	-33,65
20	-31,65	-44,98
21	-16,99	-52,31

2nd circle		
REF.	X	Y
1	2, 21	-71, 47
2	18, 63	-69, 03
3	34, 05	-62, 87
4	47, 63	-53, 33
5	58, 64	-40, 91
6	66, 5	-26, 28
7	70, 76	-10, 24
8	71, 22	6, 36
9	60, 79	37, 64
10	50, 47	50, 65
11	37, 43	60, 92
12	22, 37	67, 91
13	6, 11	71, 24
14	-10, 49	70, 73
15	-26, 52	66, 4
16	-41, 11	58, 5
17	-62, 99	33, 82
18	-69, 1	18, 38
19	-71, 47	1, 95
20	-70	-14, 58
21	-64, 75	30, 33
22	-56, 01	-44, 45
23	-44, 25	-56, 16
24	-30, 1	-64, 85


3rd circle		
REF.	X	Y
1	7, 88	-86, 6
2	23, 67	-83, 7
3	38, 65	-77, 9
4	52, 31	-69, 5
5	64, 2	-58, 7
6	73, 89	-45, 9
7	81, 07	-31, 5
8	85, 49	-16, 1
9	86, 99	-1, 14
10	85, 89	13, 87
11	80, 44	33, 15
12	73, 51	46, 33
13	64, 39	58, 51
14	52, 54	69, 34
15	38, 91	77, 82
16	23, 95	83, 64
17	8, 17	86, 62
18	-7, 88	86, 6
19	-23, 67	83, 72
20	-38, 65	77, 9
21	-52, 31	69, 51
22	-64, 2	58, 72
23	-73, 89	45, 92
24	-81, 07	31, 13
25	-85, 49	16, 56
26	-87, 0	14, 1
27	-85, 54	-15, 8
28	-81, 18	-31, 2
29	-74, 04	-45, 6
30	-64, 39	-58, 5
31	-52, 54	-69, 3
32	-38, 91	-77, 8
33	-23, 95	-83, 6
34	-8, 17	-86, 6

4th circle	REF.	X	Y
1	11, 35	-101	
2	27, 96	-98,	
3	43, 81	-92,	
4	58, 46	-84,	
5	71, 52	-73,	
6	82, 63	-66,	
7	91, 49	-60,	
8	97, 85	-54,	
9	101, 54	-10,	
10	102, 48	1, 9	
11	100, 95	17, 78	
12	95, 25	34, 87	
13	88, 23	52, 10	
14	79, 08	65, 21	
15	67, 26	77, 30	
16	53, 62	87, 34	
17	38, 51	94, 95	
18	22, 34	100, 99	
19	5, 57	102, 101	
20	-11, 35	101, 97	
21	-27, 96	98, 61	
22	-43, 81	92, 61	
23	-58, 46	84, 81	
24	-71, 52	73, 42	
25	-82, 63	66, 42	
26	-91, 49	46, 24	
27	-97, 55	31, 24	
28	-101, 28	15, 95	
29	-102, 38	4, 88	
30	-100, 39	-20, 36	
31	-95, 97	-36, 65	
32	-88, 73	-51, 55	
33	-79, 08	-65, 42	
34	-67, 26	-77, 30	
35	-53, 62	-87, 34	
36	-38, 51	-94, 95	
37	-22, 34	-100, 99	
38	-5, 57	-102, 101	


		5th circle	
		REF. X	Y
		1	5, 64
37		2	22, 74
		3	39, 35
7		4	55, 13
9		5	69, 73
2		6	82, 85
5		7	94, 2
8		8	103, 54
		9	110, 68
		10	115, 46
		11	117, 77
		12	117, 58
		13	114, 88
		14	109, 73
		15	102, 25
		16	92, 58
		17	80, 94
3		18	67, 58
5		19	52, 77
7		20	36, 84
		21	20, 13
		22	2, 98
		23	-14, 22
		24	-31, 13
		25	-47, 37
		26	-62, 6
		27	-76, 5
		28	-88, 76
		29	-99, 14
		30	-107, 4
1		31	-113, 09
2		32	-116, 64
4		33	-117, 95
6		34	-116, 38
9		35	-112, 61
2		36	-106, 27
5		37	-97, 67
8		38	-86, 99
35		39	-74, 46
		40	-60, 33
		41	-44, 93
		42	-28, 56
		43	-11, 59



Front view  
Scale: 1:1




Front view  
Scale: 1:1




Left view  
Scale: 1:1


Rear view  
Scale: 1:1




Isometric view  
Scale: 1:1



Section cut A-A  
Scale: 1:1

<b>Notes</b>	
	PCB or heatsink level.
	LED location.
	Ensure LED fitting from a product specific 3D model available from <a href="http://www.ledil.com">www.ledil.com</a> .
For more details about installation please see LEDIL Installation Guide on <a href="http://www.ledil.com">www.ledil.com</a>	

PART		TYPE MATERIAL COLOR / COATING	
Victoria HB PCB			
<b>MECHANICAL DRAWING</b>		<b>LEDiL®</b>	
PRODUCT			
VICTORIA HB			
Plastic moulding general tolerances according to DIN 8080-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 330-1 Class B and applies if not otherwise shown in the drawing.		<b>FIRST ANGLE PROJECTION:</b> 	
SCALE 1:1		WEIGHT AO SHEET 1/1	

**LEDiL®**

This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.