

iq.ul.com

Component - Plastics [\[guide info\]](#)

E56745

MOMENTIVE PERFORMANCE MATERIALS JAPAN L L C

2-20 Akasaka 5-Chome, Minato-Ku Tokyo 107-6112 JP

LSR7070(o)

Silicone Molding Resin (SIR), furnished as two liquid components

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
CL	1.0-2.2	HB	-	-	150	-	150

Comparative Tracking Index (CTI): -	Inclined Plane Tracking (IPT): -
Dielectric Strength (kV/mm): -	Volume Resistivity (10 ^x ohm-cm): -
High-Voltage Arc Tracking Rate (HVTR): -	High Volt, Low Current Arc Resis (D495): -
Dimensional Stability (%): -	

(o) - LSR7070 consists of base resin LSR7070A and hardener LSR7070B.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2002-06-21

Last Revised: 2012-10-31

© 2015 UL LLC

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	1.0-2.2	HB75 (CL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-