

RÖHM GMBH DOLIVOSTRAßE 17 DARMSTADT, 64293 Germany



PLEXIGLAS or ACRYLITE: 8N (f1)

Polymethyl Methacrylate (PMMA), pellets

- (f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.
- NOTE In the US, EVONIK ROEHM GMBH uses the designation "ACRYLITE or ROHAGLAS" instead of "PLEXIGLAS". In China, EVONIK ROEHM GMBH uses the designation "PLEXIGLAS or ROHAGLAS" instead of "ACRYLITE".

| Flammability | Value | Test Method |
|---------------------|--------|----------------------|
| Flame Rating | | |
| 1.5 mm, ALL | НВ | UL 94 |
| 1.5 mm, ALL | HB75 | IEC 60695-11-10, -20 |
| Thermal | Value | Test Method |
| RTI Elec (1.5 mm) | 90.0°C | UL 746 |
| RTI Imp (1.5 mm) | 90.0°C | UL 746 |
| RTI Str (1.5 mm) | 90.0°C | UL 746 |
| Physical | Value | Test Method |
| Outdoor Suitability | f1 | UL 746C |
| | | |

Page 1 of 1 Form Number: E507751-104111898

Report Date: 1977-07-13 Last Revised: 2019-09-17

UL and the UL logo are trademarks of UL LLC Copyright © 2020 All Rights Reserved. | www.ul.com